



DATA INFORMATION SHEET
TYPICAL PROPERTIES

DESCRIPTION:

A rigid PVC film with matte/matte surface engineered for use in the printing industry. It has good printability and consistent roughness as well as customized impact properties. Typical applications of this material include greeting cards, advertisement cards, large placards, and regular membership cards.

Special requirement options include (but not limited to):

- Customized impact strengths: HXX - high, VXX - very high, EXX - extra high
• Colors: Translucent and opaque
• *Customized formulas for special requirements.

Table with 3 columns: PROPERTIES, TYPICAL VALUES, TEST METHOD. Rows include Thickness (mils), Thickness Tolerance, Width Tolerance, Color, Gloss Value (60°), Specific Gravity, Tensile Strength (psi), Elongation (%), Heat Distortion Temp. (°F@264psi), Vicat Softening Temp. (°C), Dyne Level, Surface Roughness (Ra, microinch), Impact Strength, Gardner Drop (in-lbf/mil): Opaque, Cold-Break Temperature: Translucent, UV Resistance.

* For dimensions and/or physical properties different from what listed above or special requirements including weatherability and flammability etc., contact the vendor for the agreement on the specifications.

** Proprietary Vendor Product Inspection and Test Methods

Product Performance and Suitability Disclaimer

All descriptive information, performance data, and recommendations for the use of Masterpiece Graphix (MGX) products shall be used as a guide only, and do not reflect the specification or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute an MGX company warranty of any kind.