



.004 White Vinyl/Low Tack Removable/94#

MGX-2076

13" x 19"

1500 FENPARK DRIVE, FENTON, MO 63026 P: 636.349.6401 F: 636.349.6402 MGXDIGITAL.COM SALES@MGXDIGITAL.COM

- Low tack, removable pressure-sensitive adhesive bonds well to smooth non-tinted glass surfaces while removing cleanly
- Adhesive adheres well to an exterior glass surface over a wide range of temperatures

PRODUCT DATA	VALUE		TEST METHOD
Physical Properties			
Thickness (Mils[microns])			ASTM D 3652 (Modified for use with non-tape products)
	Film	3.5 (89) +/- 10%	
	Adhesive	0.8-0.9 (20-23) +/- 0.1 (3)	
	Liner	6.9 (175) +/- 10%	
Dimensional Stability (%)			Applied shrinkage: 24 hour dwell time on aluminum panel then 24 hours at 160°F (71°C)
	MD	0.50	
	TD	0.50	
Adhesion Properties			
Ultimate Peel from	Average Oz/In	(N/m)	ASTM D 903 (Modified for 72 hour dwell time)
Non-tinted Glass	13	(143)	
Tack (gm/sq cm)	70		ASTM 2979
Expected Exterior Life	Two years		
Service Temperature Range	-20°F to 176°F (-29°C to 80°C)		
Minimum Temperature Storage	50°F (10°C)		
Application Stability	2 years when stored at 70°F (21°C) & 50% relative humidity		

Product Performance and Suitability Disclaimer

All descriptive information, performance data, and recommendations for the use of Masterpiece Graphix (MGX) products shall be used as a guide only, and do not reflect the specification or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute an MGX company warranty of any kind. All purchasers of MGX products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of MGX is authorized to give any warranty, guarantee, or make any representation in addition or contrary to the above.