

## **MGX-2523**

## 2 mil Bright Silver Polyester ID / Permanent / 90# 0-Split 12" x 18"







Adhesive: Permanent



Liner: 90# 0-Split

## **DESCRIPTION:**

MGX's 2.0 mil bright silver polyester provides aggressive permanent adhesive bonds well to low- and high-surfaces including painted metal, powder-coated paint and plastics. Backed with a lay-flat liner.

## **APPLICATIONS:**

Brand Labels • Electronics • Appliances • Automotive • Industrial Equipment

	Physical Properties	Value	Test Method
FACESTOCK	Thickness	2 mils (Range +/- 10%)	ASTM D 3652 (Modified for non-tape products)
	Dimensional Stability	No Shrinkage Observed	24 HR dwell time on aluminum panel then 24 HR at 160°F
ADHESIVE	Adhesive Thickness	0.9-1.0 (Range +/-10%)	ASTM D 3652 (Modified for non-tape products)
	Ultimate Peel		
	ABS	60 oz/in	ASTM D 903 (Modified for 72 HR Dwell Time)
	Acrylic	77 oz/in	
	Acrylic Powder Paint	59 oz/in	
	Aluminum	54 oz/in	
	Epoxy Powder Paint	67 oz/in	
	Glass	68 oz/in	
	HDPE 32	32 oz/in	
	Painted Metal	57 oz/in	
	Polycarbonate	58 oz/in	
	Polyester	87 oz/in	
	Polyester Powder Paint	55 oz/in	
	Polypropylene	15 oz/in	
	Polyurethane Powder Paint	72 oz/in	
	Stainless Steel	55 oz/in	
	Styrene	54 oz/in	
	Room Temp	30 hours	
	Tack	1030 gm/sq	ASTM D 2979
	Service Temperature Range	-40°F to 302°F	
	Minimum Application Temperature	50°F	
	Storage Stability	Store at 70°F (21°C) and 50% relative humidity	
LINER	Liner Thickness	6.9 +/- 10%	ASTM D 3652 (Modified for non-tape products)