

## MGX-5062

## 60# Semi-Gloss MP / Permanent / 85# Scored 13" x 19"







Adhesive: Permanent



Liner: 85# Scored

## **DESCRIPTION:**

MGX's 60# Semi-Gloss is optimized for HP Indigo presses. It has high brightness and is highly opaque with exceptional gloss level. The base sheet is elemental chlorine free and lignin free. Great ink adhesion and optimal strength for die cutting and matrix stripping. The permanent cold temperature emulsion acrylic adhesive has good initial tack and good adhesion to a wide variety of surfaces. Backed with a clay-coated bleached kraft liner with pre score marks 1-1/4" apart.

## **APPLICATIONS:**

Rigid Plastics • Films • Glass • Painted Metals

	Physical Properties	Measure	Value
FACESTOCK	Caliper	mils	3
	Opacity	%	91
	Brightness	%	90
	Tensile MD	lb	35
	Tensile CD	lb	17
	Tear MD	g	30
	Tear CD	g	30
	Regulatory Compliance	CA Prop. 65, RoHS, REACH	
ADHESIVE	Туре	Permanent Emulsion Acrylic	
	Thickness	mils	0.6
	Min. Application Temp	°F	35°
	Service Temp Range	°F	-10° to +200°
	Regulatory Compliance	RoHS, REACH	
LINER	Caliper	mils	4.6
	Opacity	%	86
	Tensile MD	psi	36
	Tensile CD	psi	21
	Regulatory Compliance	CA Prop 65, RoHS, REACH	

Product Performance and Suitability Disclaimer: All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own test. MGX shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.